



farsouth
networks

BROCHURE



wanderbox

ACTUAL PRIVATE SERVER (APS)

7 Wanderbox 3CX PBX Servers

50 users, 32 calls EACH

High density, datacentre installations

Low power consumption

Multi-tenant deployments



✓ 7 IN ONE

3CX
DISTRIBUTOR

Copyright © 2007-2021 Far South Networks (Pty) Ltd
www.farsouthnet.com



farsouth
networks

Product Brief

Each Wanderbox APS unit integrates 7 individual Wanderbox 3CX PBX servers
Available in a rack mount package, ideal for datacentre environments
High density, 3CX PBX installations
Low power consumption, low heat footprint

Accessible via DHCP, each 3CX PBX server is identifiable via unique MAC address and Serial number combination
Each Wanderbox 3CX PBX server is pre-installed with 3CX PBX software and a 3CX 4SC Standard (non-commercial) license
Upgradable to a maximum 32 simultaneous call Standard, Professional or Enterprise 3CX license

Utilise the companion Wanderbox SBC for simple customer installations and improved quality voice calling

Feature Summary

Rack mount, 1U x 19" package

Capacity per Wanderbox PBX unit:

- 50 Users: IP phones, Mobile App & Soft clients
- 32 simultaneous calls (selectable from 4, 8, 16, 24, 32)
- Storage: 32GB (upgradable to 64GB, 128GB on order)

Hardware

- AC Power: 110V/230Vac, 50Hz (C14, kettle plug) input
- Power consumption: 100W (max)
- Front panel, visual indications:
 - Power LED
 - 7 x Network status LED
- Dimensions: 437mm x 280mm x 44mm
- Power On/Off switch (internal 3CX servers power cycle under software control)

WAN port:

- RJ-45
- Gigabit Ethernet

Network Protocols and Services: PPP, IPv4, HTTPs

Routing: Static, DHCP

Reference Documents

Wanderbox micro datasheet: <https://bit.ly/3cM81ET>

Wanderbox Wiki: <https://sites.google.com/view/3cx-pbx-appliance-wiki>